

# MATERIAL SAFETY DATA SHEET

REM-KS-901

SECTION I - PRODUCT IDENTIFICATION				
PRODUCT	SEAMFIL 901 White and all colors		DATE	January 2010
MANUFACTURER	Kampel Enterprises, Inc.			
ADDRESS	8930 Carlisle Road, Box 157			
CITY, STATE	Wellsville, PA			
ZIP	17365-0157	EMERGENCY TELEPHONE	1-800-457-4280 / 1-352-323-3500	
PROPER SHIPPING NAME	Resin Solution	DOT HAZARD CLASS	Flammable Liquid - UN 1866	CAS NO. Mixture
NFPA / HMIS INFORMATION				
SHIPPING CLASSIFICATION GROUND ONLY	HEALTH	2	FLAMMABILITY	3
	REACTIVITY	0	PROTECTION	G
	ORM-D			

SECTION II - HAZARDOUS INGREDIENTS				
CAS NO.	HAZARDOUS INGREDIENT	WT. % is less than (Vol.)	OSHA PERMISSIBLE EXPOSURE LLIMIT (PEL) TO,E WEIGHTED AVERAGE (TWA)	ACGIH THRESHOLD LIMIT VALUE (TLV) TIME EIGHTED AVERAGE
108-88-3	Toluene (Methyl Benzene)	11	100 ppm	100 ppm
67-64-1	Acetone (2-Propanone)	6	750 ppm	750 ppm
78-93-3	Methyl Ethyl Ketone (2-Butanone)	13	200 ppm	200 ppm
108-65-6	1-Methoxy 2-Propanol Acetate	5	N / EST	N / EST
115-86-6	Triphenyl Phosphate	6	3 mg / m3	3 mg / m3
7732-18-5	Water	1	N /EST	N /EST
Materials listed for this product are on the TSCA inventory list.				

SECTION III - PHYSICAL DATA					
APPEARANCE , ODOR	Very viscous white or colored liquid with an aromatic odor				
SPECIFIC GRAVITY @ 60° F	1.23 (water=1); WPG: 10.26	VAPOR PRESSURE (mm/hg):	180	FREEZING POINT	N/ A
PERCENT VOLATILE (VOC) BY WT	48 (529 g voc/L)	VAPOR DENSITY	> 1 (Air = 1)	EVAPORATION RATE	Slower than –butyl Acetate
AUTO IGNITION TEMPERATURE	N/A	BOILING RANGE @760 mmHg	131° to 473° F	MELTING POINT	N / A
SOLUBLE IN WATER	11.0 % Soluble	VOCS, lbs./Gal.	Minus exempt: 3.52	VOLATILE BY VOL.	72.1%
VOLATILE BY WEIGHT	54.5%			VOCS, grams/ltr.	529 g voc / L

SECTION IV - FIRE AND EXPLOSION HAZARD DATA					
FLAMMABLE (Y/N)	Yes	UNDER WHAT CONDITIONS?	Oxidizers, sparks & open flame		
EXPLOSIVE (Y/N)	Yes	UNDER WHAT CONDITIONS?	Closed containers exposed to extreme heat, or sparks from welding, static, etc.		
MEANS OF EXTINCTION	NFPA Class B Extinguisher (Co <sub>2</sub> or Foam) for Class 1 B fires		HAZARDOUS PRODUCTS OF COMBUSTION	Carbon Monoxide, Carbon Dioxide	
FLASHPOINT AND METHOD	1 ° F	UPPER FLAMMABLE LIMIT, IN AIR	12.8% (Vol)	LOWER FLAMMABLE LIMIT, IN AIR	1.0% (Vol)
SPECIAL PROCEDURES	Use bunker gear and breathing apparatus. Eliminate sources of ignition. Using fog nozzles, spray water to protect firefighters, reduce vapor build-up, and cool containers.				

SECTION V - REACTIVITY DATA				
CHEMICAL STABILITY	Stable	UNSTABLE UNDER WHAT CONDITIONS?	N/A	
INCOMPATIBLE WITH OTHER SUBSTANCES (Y/N?)	Yes	INCOMPATIBLE WITH WHICH PRODUCTS?	Strong oxidizers, acids and bases	
HAZARDOUS POLYMERIZATION	Will not occur	HAZARDOUS PRODUCTS OF DECOMPOSITION	None	

SECTION VI - TOXICOLOGICAL DATA	
-NATURE OF HAZARDS DUE TO EXPOSURE-	
EYES Irritates strongly.	SKIN Irritates. May cause dermatitis due to drying.
RESPIRATORY Irritates mucous membranes. Prolonged exposure may cause lung damage.	ORAL Regurgitation may cause respiratory pneumonia.
OTHER Acute exposure may cause nervous system depression, producing headache, dizziness, nausea, or loss of consciousness. Prolonged exposure may cause damage to kidneys, lungs, nerves, or liver.	

SECTION VII - HANDLING PRECAUTIONS		
-PROTECTIVE EQUIPMENT-		
GLOVES Impervious to organic solvents	RESPIRATOR OSHA approved. Charcoal filter as minimum	EYEWEAR Chemical goggles
FOOTWEAR Impervious boots	CLOTHING Chemical apron	FACILITY Explosion proof equipment
CONDITIONS TO AVOID Avoid eye contact. Minimum skin contact, breathing of vapors.		
-SPILL PROCEDURES-		
SMALL SPILL OR LEAK Eliminate sources of ignition. Use absorbent material and transfer to DOT container. Contact approved Haz Mat Emergency for disposal.		
LARGE SPILL Isolate from oxidizers, heat and sources of ignition (see Protective Equipment). Stop spill, and dike area to prevent spread; pump liquid to salvage tank. Contact local Haz Mat emergency response team.		
-STORAGE AND DISPOSAL PROCEDURES-		
TRANSFER METHOD Ground containers and limit freefall distance to prevent static spark. Prevent vapor accumulation; close containers, ventilate area.		
TEMPERATURE RANGE 0 ° F to 120 ° F	WAREHOUSING Store in structures made for OSHA Class 1 B liquids.	
DISPOSAL Observe Federal, State, and Local regulations. Recycle spent solvent in approved equipment. Contact RCRA approved Hazardous Waste Recycling/Disposal Facility.		

SECTION VIII - FIRST AID	
EYE CONTACT	Flush with water for 15 minutes. Get medical attention.
SKIN CONTACT	Wipe excess liquid with towel, wash with soap and water. Use moisturizers before and after exposure.
INHALATION	Remove to fresh air. Give oxygen if breathing is difficult, artificial respiration if breathing has stopped.
INGESTION	Call a physician immediately. Do not induce vomiting, as aspiration into lungs may be fatal. Do not give liquids. If vomiting occurs, keep head below hips to prevent aspiration.

SECTION IX - ENVIRONMENTAL PROTECTION			
-APPLICABLE LAWS AND GOVERNMENT AGENCIES-			
TRANSPORTATION REQUIREMENTS	49 CFR, Parts 100 through 177	EMPLOYEE PROTECTION REQUIREMENTS	29 CFR, Parts 1900 through 1926 (OSHA Hazard Communication Standard)
WORKER & COMMUNITY RIGHT TO KNOW, AND EMERGENCY PLANNING	SARA (Superfund Amendments and Reauthorization Act) Title III	EMERGENCY RELEASE REQUIREMENTS	EPA 40 CFR, Part 117; CERCLA (Federal Superfund), National Response Center, SARA
FEDERAL CLEAN AIR REQUIREMENTS	EPA, Clean Air Act and Amendments of 1990	STATE CLEAN AIR REQUIREMENTS	PA Air Pollution Control Act, or equivalent
FEDERAL HAZARDOUS CHEMICAL REPORTING REQUIREMENTS	CERCLA (Comprehensive Environmental Resource & Conservation Liability Act) for substances above reportable threshold	STATE HAZARDOUS CHEMICAL REPORTING REQUIREMENTS & EMERGENCY PLANNING	SARA Section 312 Reporting of facility's chemical inventory to State Emergency Response Commission, and Local Emergency Planning Committee

-CERCLA / SARA ENVIRONMENTAL REPORTING-								
INGREDIENT	TYPICAL PERCENT (Wt.)	VOLATILE ORGANIC COMPOUND (VOC)?	SARA Section 302		SARA Section 313		CERCLA REPORTABLE QUANTITY	CARCINOGEN?
			REPORTABILITY QTY. OF EXTREMELY HAZARDOUS SUBSTANCE	THRESHOLD PLANNING QUANTITY	TOXIC CHEMICAL?	CATEGORY FOR TOXIC RELEASE INVENTORY		
Petroleum Solvent	1	Yes	Not EHS	N/A	No	None	N/A	No
Toluene	15	Yes	Not EHS	N/A	Yes	None	1000 lbs	Yes
Xylene	8	Yes	Not EHS	N/A	yes	None	1000 lbs	No
Acetone	7	Yes	Not EHS	N/A	Yes	None	5000 lbs	No
1-Methoxy-2-Propanol Acetate	3	N/A	Not EHS	N/A	No	None	N/A	No
SARA SECTIONS 311, 312 HAZARD CATEGORY (H-1=ACUTE HEALTH; H-2 = CHRONIC HEALTH; P-3 = FIRE; P-4 = PRESSURE; P-5 = REACTIVE);								
				H-1, H-2, P-3				

The above information is offered in good faith for usage under typical conditions. Recommendations should be reviewed to determine the applicability of this information in the context of intended usage.